

# **PROJECT SUMMARY (DESCRIPTION & MAP)**



---

# PROJECT SUMMARY

---

HAZARDOUS WASTE DESTRUCTION - INCINERATION



FEBRUARY 11, 2025  
PURAN BROTHERS DISPOSAL INC.  
LOT 7 BELLA DAM, KLIEN POWDEROYEN, WBD

# Contents

<b>INTRODUCTION</b> .....	2
<b>PROJECT LOCATION</b> .....	2
<b>PROJECT DESCRIPTION</b> .....	5
<b>Waste Acceptance</b> .....	5
<b>Waste Rejection</b> .....	6
<b>Transportation of Hazardous Wastes</b> .....	7
<b>Record Keeping</b> .....	8
<b>Waste Receipt</b> .....	8
<b>WASTE DESTRUCTION (INCINERATOR)</b> .....	13
<b>Incineration Process</b> .....	15
<b>POTENTIAL ENVIRONMENTAL IMPACTS AND MITIGATION MEASURES</b> .....	17
<b>Air Emissions from Hazardous Waste Incineration</b> .....	17
<b>Operation Mitigation / Control Measures</b> .....	18
<b>CONCLUSION:</b> .....	21

## INTRODUCTION

Puran Brothers Disposal Inc. is an incorporated waste management company with over 35 years of experience in the sector. The company's diverse operations include the collection, transportation, and treatment of hazardous and non-hazardous wastes across six of Guyana's ten administration regions: 2, 3, 4, 5, and 6.

The Company intends to expand its operation to include hazardous waste destruction via incineration at Lot 'S' Mary, Nouvelle Flanders, La Jalousie Village, West Bank Demerara (WBD).

To ensure compliance with environmental regulations, Puran Brothers Disposal Inc. is seeking environmental authorization from the Environmental Protection Agency (EPA) for the new operation at Mary, WBD. This Project Summary supports the application.

## PROJECT LOCATION

Puran's Hazardous Waste facility will be located at Lot 'S' Mary Nouvelle Flanders, La Jalousie Village, WBD within 1.5 acres of land that was previously a part of a rice milling complex. The intended project area is currently unoccupied and covered by thick underground vegetation.

The Project Area of Influence (AOI), which is relative to the immediate and surrounding areas distinguishes between the area of direct influence (ADI) and the area of indirect influence (**AI**). The ADI includes the area occupied by the Project, while the **AI** includes surrounding areas. While different AOIs will have varying degrees of impact, a standard AOI of 500 meters (0.3 miles) was established for ease of reference.

Within the project's Area of Indirect Influence are agricultural industrial activities such as the rice milling complex located immediately north and rice farms to the west and south of the site. Approximately 75% of the area of indirect influence is rice farms. Residents accounting for 20% of the area of indirect influence are located to the north and east (upwind) of the project location. The closest resident is located 24 meters east of the project.

The nearest major water body to the project is the Atlantic Ocean approximately 1000 meters north. Notwithstanding the aforementioned, the rice fields are dissected by canals that collect water from the fields and discharge it into the ocean. The closest canal to the project location is 124 meters south.

The layout of the project referenced in Figure 3 indicates that the hazardous waste facility will be operating from a highly ventilated, semi-enclosed warehouse with three sides, a retracting aluminum door, and a zinc roof. The incinerator will be at the northern section of the warehouse. The incoming waste for destruction will be staged within the warehouse or openly depending on the conditions or the quality of the waste storage container.



Figure 1: Google map of the Project Location



Figure 2: Current condition of the project location



## PROJECT DESCRIPTION

Puran's Hazardous Waste Destruction project intends to dispose of hazardous wastes via the incineration process. The industrial waste incinerator to be installed at the project will incinerate or burn at 650°C – 1100°C high temperature.

### Waste Acceptance

Wastes accepted by the project for destruction will include hazardous and non-hazardous solids, and semi-solids including oily sludge, bio-hazardous waste, hydrocarbon-contaminated solids, etc. However, all waste must undergo a **rigorous pre-acceptance and pre-receipt process** to ensure compliance with facility and regulatory standards.

#### *Pre-Receipt Procedure*

Before waste is transported to the project site, customers must submit a **Waste Generator Information Sheet (WGIS)**. The project team will review the submitted information to determine whether the waste can be accepted for destruction or if it must be rejected. This step is essential to ensure that only approved waste enters the facility.

#### 1. Generator-Supplied Information

For each new batch of waste, the generator must provide the following details and supporting documentation:

##### **Waste Profile Sheet (WPS)**

The Waste Profile Sheet (WPS) contains critical physical and chemical data required to characterize the waste. At a minimum, the waste generator must supply all necessary information to ensure the waste is suitable for destruction.

##### **Standard Waste Profiles**

In some cases, a standard profile may be used for multiple waste streams that share similar physical and chemical characteristics. Standard profiles are only applicable when the following criteria are met:

**Generating Process** – The waste-generating process must be described in detail. For example, if the waste originates from a Liquid Mud Plant (LMP), the description must specify which section or process within the LMP produced the waste.

**Raw Ingredients Used in the Generating Process** – The waste profile must include a complete list of raw materials used in the process that generates the waste.

#### 2. Waste Sampling and Analysis

A **representative sample** is required for all waste streams, with limited exceptions. The sample will undergo laboratory testing to confirm its characteristics. Table 01 outlines the parameters to be analyzed during pre-acceptance.

#### **Additional Supporting Documentation**

Depending on the nature of the waste, additional documentation may be required to supplement the Waste Profile Sheet and waste sample analysis. This may include:

**3. Material Safety Data Sheet (MSDS)** – Provides additional details on the chemical composition and hazards associated with the waste.

**Analytical Results** – Any previously conducted tests that provide insight into the composition and properties of the waste.

#### **4. Final Approval and Waste Delivery**

Once the facility reviews and approves the waste for destruction:

The waste generator will receive confirmation that the waste is approved for transport.

The waste must be delivered under regulated conditions in compliance with safety and environmental guidelines.

Upon arrival, the waste will be inspected again before being processed for destruction.

This structured pre-receipt and pre-acceptance process ensures compliance with environmental regulations, enhances safety, and optimizes the facility's waste management efficiency.

#### **Waste Rejection**

The project will not incinerate plastic waste, including types such as polyethylene (PE), polypropylene (PP), polyvinyl chloride (PVC), and polyethylene terephthalate (PET), as these plastics release harmful toxins when burned.

When plastic waste, especially types like polyethylene (PE), polypropylene (PP), polyvinyl chloride (PVC), and polyethylene terephthalate (PET), is burned or improperly disposed of, it can release harmful toxins into the environment. These toxins can have severe health and environmental impacts. Some of the most harmful toxins produced include:

1. **Dioxins:** These are highly toxic compounds that are produced during the combustion of chlorine-containing materials like PVC. Dioxins can accumulate in the food chain, posing significant risks to human health, including cancer, reproductive and developmental damage, immune system suppression, and hormonal disruption.
2. **Benzene:** A carcinogenic compound that is released when plastics such as PET are burned. Prolonged exposure to benzene can lead to leukaemia, blood disorders, and other serious health issues.
3. **Polychlorinated Biphenyls (PCBs):** These are toxic chemicals that can be released during the burning of certain plastics. PCBs are persistent in the environment and can accumulate in living organisms, leading to long-term health issues such as cancer, immune system suppression, and developmental disorders.

4. **Carbon Monoxide:** This colorless, odorless gas is produced when plastic materials, especially those with high carbon content, are incompletely burned. Exposure to carbon monoxide can lead to headaches, dizziness, confusion, and, in extreme cases, death.
5. **Hydrogen Chloride:** When PVC plastics are burned, hydrogen chloride is released, which can cause respiratory issues, irritation of the eyes, and long-term damage to lung tissue.
6. **Particulate Matter:** Burning plastics can also release tiny particles into the air, which can lead to respiratory problems, and cardiovascular issues, and exacerbate existing conditions like asthma.

These toxins can have lasting effects on both human health and the environment, which is why proper plastic waste management and disposal are critical. Avoiding incineration and promoting recycling or other environmentally friendly disposal methods helps reduce the release of these harmful substances.

Additionally, the facility is not equipped to process nuclear or radioactive waste. These types of waste will not be accepted at the facility. If such waste is inadvertently received without prior indication from the generator and is identified during the screening process, the generator will be notified, and the waste will be promptly returned. Incinerating plastic waste can contribute to air pollution, including the release of dioxins, furans, and other toxic chemicals that negatively impact air quality and pose serious risks to human and environmental health.

### **Transportation of Hazardous Wastes**

Whereby the hazardous waste generator is transporting its waste to the project location, the generator must ensure that the waste is secured and appropriately packaged. The transporter will have to ensure that the appropriate journey management plans are prepared, emergency response measures are in place before transportation, and that wastes are stored in closed containers at all times.

Where the waste is transported by the project primarily in hazardous waste skips, the project will ensure the following:

1. Storage skips are adequate i.e., can withstand corrosiveness, have adequate capacity, lining or seals in place, etc.
2. Safety Data Sheets (SDS) are provided by the generator. If SDS is unavailable, sufficient information is obtained from the generator regarding the characteristics of wastes, particularly corrosive, reactive, ignitable, or toxic. These properties are listed on the label of the storage medium.
3. The waste manifest document must be completed and must be signed by the generator. The project will not accept any hazardous waste unless a completed and detailed WGIS is provided.

### **Transportation of Sludge (semi-solid) by the Project**

Semi-solid wastes will be transported in specially designed bins which are sealed to prevent spillage during transport. The bins are designed with forklift slots to facilitate easy loading and offloading.

### **Record Keeping**

The transport crew will maintain daily field logs. Each daily log will include the date, time, weight/volume, waste/material, truck plate number, driver, and escort vehicles used for each trip. Daily field logs will record the following information:

1. Truck Identification and Company
2. Time scheduled in, or arrival upon return.
3. Manifest Number.
4. Waste type loaded
5. Waste Generator's Location
6. Estimated waste quantity entered on the manifest.
7. Time departed from the Loading Site
8. The time arrived at the Project Location
9. Notes – any incidents or problems during transport.

Hazardous wastes, as per EPA regulations must be accompanied by a Hazardous Waste Manifest that will be signed by both the transporter and the waste generator.

All manifests and shipping documents will be carried in the truck cab within reach of the driver. Other documents furnished to the driver with each load will include either a map or driving directions specifying the approved transportation routes. Drivers will be furnished with a checklist summary of the Transportation Plan and will receive a health and safety briefing. A copy of the Transportation Plan will also be available at the Project.

### **Waste Receipt**

#### Verification of Incoming Shipments

Verification of incoming waste involves inspection upon entry onto the project site.

#### Visual and Chemical Inspections

The container receipt inspection is a mandatory element of the confirmation process. Therefore, 100 % of the incoming waste will be inspected and physically verified for damage to ensure the waste containers are those indicated on the documentation. The numbers on the waste transport bins must match the numbers listed on the manifest.

During the inspection, at least one container from each profiled waste will be opened and its contents will be visually inspected to confirm it matches the physical description on its profile.

The visual inspection will address color, viscosity, and waste form (e.g., debris, PPE, sludge), at a minimum.

Upon receipt of the wastes, a representative from the Project will collect the necessary WGIS and SDS and verify the incoming wastes against the information submitted in the aforementioned documents. The verification process will entail the measurements of both the physical and chemical properties such as weight, color, consistency (liquid, solid, sludge, powder), pH, etc. which is critical for determining which treatment is applicable for the waste

For waste streams that cannot be identified by the SDS due to physical and chemical changes from the process they were exposed to, the project will require lab testing to be conducted to classify the incoming waste. Waste testing includes:

1. In-house testing with rapid test kits would allow for the profiling of waste streams.
2. Lab testing with local and regional accredited labs to re-evaluate ongoing incoming waste
3. Gas testing/headspace analysis (includes Volatile Organic Compounds (VOCs), Carbon Dioxide (CO<sub>2</sub>), Hydrogen Sulphide (H<sub>2</sub>S), Benzene and Lower Explosion Limit)

#### Discrepancy Resolution

If the mandatory verification of incoming waste identifies a discrepancy with the Waste Profile Sheet (WPS), and the discrepancy cannot be resolved by the generator, then the project will perform **supplemental analysis** of the waste, reject the waste, or send the waste to an alternate treatment, storage, or disposal facility. A possible discrepancy may include any of the following:

1. A generator notifies the project that the process of generating the waste has changed.
2. The results of inspection or analysis indicate that the waste received at the project does not match the identity of the waste designated on the accompanying manifest or acceptance documentation.

#### Supplemental Verification

Any waste that is subject to a supplemental analysis will be quarantined until the discrepancy with the WPS is resolved. Supplemental analysis will be subcontracted to an independent testing facility approved by the EPA. The results of all supplemental analyses will be documented in a log maintained as part of the project operating record.

#### Final Acceptance

Upon verification that a batch of waste is consistent with the corresponding Waste Profile Sheet, the waste will be moved from the receiving area to an appropriate staging area in preparation for treatment and/or disposal. Any waste that does not conform to the corresponding WPS will

be quarantined until the discrepancy is resolved with the generator. Upon resolution of the discrepancy, the waste will be moved to an appropriate staging area for processing.

#### Waste Labelling and Segregation

Waste inspection information will be recorded on a waste log before the waste is labeled and transported to a relevant storage area for treatment. Wastes will be labeled to allow for identification and placement in designated storage/staging areas. The information included on the label is as follows:

1. Source of waste (generator, generation process)
2. Date of receipt
3. Volume
4. Physical description (solid, liquid)
5. Chemical characteristics/properties (acidic, flammable, corrosive, etc.)
6. Expiration date, where applicable

**Table 01: Post Treatment Tests and Testing Parameters**

Tests Conducted	Rationale	Parameters
TCLP Metals	Determines the concentration of leachable metals in the waste stream (arsenic, barium, cadmium, chromium, lead, mercury, silver, and selenium)	TCLP Extractable Arsenic (mg/L) 5.0 mg/l <sup>3</sup> TCLP Extractable Barium (mg/L) 100 mg/l <sup>3</sup> TCLP Extractable Cadmium (mg/L) 1.0 mg/l <sup>3</sup> TCLP Extractable Chromium (mg/L) 5.0 mg/l <sup>3</sup> TCLP Extractable Lead (mg/L) 5.0 mg/l <sup>3</sup> TCLP Extractable Mercury (mg/L) 0.2 mg/l <sup>3</sup> TCLP Extractable Selenium (mg/L) 1.0 mg/l <sup>3</sup> TCLP Extractable Silver (mg/L) 5.0 mg/l <sup>3</sup> TCLP Extractable Zinc (mg/L) 10 mg/l <sup>3</sup>
Faecal Coliform	To determine the quantity of faecal matter present in the waste stream	<400 CFU/100ml
TSS	To determine the level of treatment (sedimentation & filtration) required to meet the discharge criteria.	<50 mg/L
BOD	Is used to capture the oxygen consumption for biological degradation of organic matter.	< 50 mg/L

pH	To determine the level of acidity/alkalinity of the waste and the associated corrosively.	5.0-9.0
TPH	Determine the level of Petroleum Hydrocarbons in the waste.	< 40 mg/L
Oil & Grease	Is used to determine oil and grease concentrations	< 10 mg/L
Volatile Organics	Determines if the waste is potentially listed (e.g., contains a volatile organic compound potentially used as a solvent) and if the concentration of any volatile organic compound exceeds the limits	Tested for presence.
Flash Point	Indicates the fire-producing potential of the waste and determines whether the waste is RCRA-ignitable	>93°C
Retort Analysis	Used for determining oil, water, and solids content in the mud, comprising a sample chamber assembly of known volume filled with mud	Tested for presence.
Chlorinated Organics	Test Chlorinated organic carriers are chlorinated organo benzenes, toluenes, and their isomers. These chemical compounds pose potential health risks to human health	Tested for presence.
Specific Gravity/Density	As a verification of the physical property of the waste as referenced on the SDS.	N/A

All ash recovered after destruction will have an analytical test result showing that the waste is within acceptable levels.

## WASTE DESTRUCTION (INCINERATOR)

### Incinerator Specification

Model: GB 18484-2001 / HJ-T177-2005 "Construction Technical Specifications for Waste Centralized Incineration Disposal"

Incineration capacity: 100kg/Batch

Average calorific value: 2500-3000kcal / kg

Items	Specification
Furnace Body	Material: Q235 steel and high-quality refractory insulation material  Refractory material thickness: <b>280mm</b> Q235 material thickness: <b>6mm</b>
Secondary combustion chamber and mixed combustion chamber	Material: Q235 steel and high-quality refractory insulation material  Refractory material thickness: <b>250mm</b> Q235 material thickness: <b>6mm</b>
Gasification room	Material: Q235 steel and high-quality refractory insulation material  Refractory material thickness: <b>165mm</b> Q235 material thickness: <b>6mm</b>
Chimney	Dimensions: 280*6000mm Material: Q235 steel anti-corrosion material
Air blower	Model: 9-19 5A Power: 0.55kw
First combustion chamber burner	Brand name: Balte brand Power: 0.18kw
Secondary combustion chamber burner	Brand name: Balte brand Power: 0.25kw
Wet scrubber	Type: High-pressure jet type Temperature at the outlet: 78-80 degrees
Water recycling pump	Power: 1.5kw Brand: Nanfang

Dust remove device	Type: Cyclonic Application: to separate water droplets from flue gases  Material of construction: Mild steel rubber lined 3mm thick
Fan	Type: High-pressure centrifugal Drive: Belt driven Power: 3kw




Figure 4: Incinerator illustration



Figure 5: Incinerator

## Incineration Process

### *Process Technology*

Before starting the furnace, the operator must activate the pilot fan to purge any residual combustible gases. Once this step is complete, other motorized equipment can be operated.

Waste is then fed into the furnace, where ignition is initiated. After ignition, the blower is activated, allowing the waste to combust using its calorific value. Under the influence of high-pressure combustion air, the waste undergoes complete combustion. At furnace temperatures ranging from 650°C to 1000°C, the waste is thoroughly burned and decomposed.

The secondary combustion chamber functions as a gas-burning furnace. Unburned gases from the main furnace enter this chamber, where they undergo complete combustion in a high-temperature environment. Following the "three T" principle in design, the furnace temperature is maintained at or above 1100°C. The gases remain in the high-temperature zone for at least 2 seconds, ensuring the complete decomposition of harmful substances.

The high-temperature flue gas produced by incineration first passes through a water-cooling device, where its temperature is lowered. It then moves to a wet scrubber, which sprays water to further cool the gas and remove large impurity particles. After this, the gas enters a cyclone dust collector, which eliminates most of the remaining dust particles. This ensures efficient dust

removal, allowing the subsequent equipment to function properly. The overall removal efficiency for dust particles larger than 100  $\mu\text{m}$  exceeds 90%.

***Wet Scrubber:***

Water or lime water (which is more effective) is used to spray the flue gas, removing large floating particles and impurities. This process reduces the workload on subsequent equipment and extends the service life of the cyclone dust collector. The water used in the wet scrubber is continuously recycled through filtration, ensuring no water pollution.

***Cyclone Dust Collector:***

Working Principle:

When medical waste is incinerated, the resulting gases generate dust, which is drawn into the cyclone dust collector by an induced draft fan. The cyclone dust collector separates particulate dust from the airflow using centrifugal force. The upper part of the collector is conical in shape.

As the dust-laden gas enters through the spiral intake pipe at the upper side of the cylinder, it encounters a reverse spiral wind. This causes the dust particles to separate efficiently from the gas stream.

The discharged dust particles settle into the dust collector. The dust collection system is designed to capture dust particles from the flue gas produced during garbage incineration. This ensures easy maintenance and helps maintain the efficiency of subsequent equipment.

***Pre-ignition and Combustion***

Before igniting the waste, operators purge the furnace to remove residual combustible gases, ensuring the combustion process starts safely and efficiently. Once the furnace is purged, motorized equipment is activated, and waste is fed into the furnace.

***Combustion Process:***

The waste is ignited, and once the initial ignition is successful, the blower system is engaged. The combustion process relies on the waste's calorific value to sustain combustion. Combustion air is introduced under high pressure to facilitate the breakdown of the waste.

Temperatures are maintained between 650°C to 1000°C in the furnace to ensure efficient burning and decomposition. At these temperatures, most organic materials undergo complete oxidation, breaking down into simpler substances like carbon dioxide, water vapor, and heat.

## POTENTIAL ENVIRONMENTAL IMPACTS AND MITIGATION MEASURES

This section identifies and describes the potential adverse environmental impacts of the project. Mitigation measures are described in detail to reduce or mitigate the identified impacts.

Incineration is commonly used for the disposal of **hazardous waste**, such as industrial chemicals, medical waste, petroleum refinery sludge, and contaminated materials. However, burning hazardous waste generates several **byproducts** that require proper management to prevent environmental contamination.

### Air Emissions from Hazardous Waste Incineration

The primary concern with hazardous waste incineration is the release of toxic gases and particulates. These emissions depend on the type of waste, combustion efficiency, and pollution control systems in place.

#### Key Air Pollutants:

Pollutant	Source	Environmental & Health Effects
Carbon Dioxide (CO <sub>2</sub> )	Combustion of organic materials	Greenhouse gas contributing to climate change
Carbon Monoxide (CO)	Incomplete combustion of carbon-based waste	Toxic gas that reduces oxygen in the bloodstream
Nitrogen Oxides (NO <sub>x</sub> )	Combustion of nitrogen-containing compounds	Contributes to smog, acid rain, and respiratory issues
Sulfur Oxides (SO <sub>x</sub> )	Burning sulfur-rich waste (e.g., oil-based products)	Forms acid rain, damaging ecosystems
Dioxins and Furans	Incineration of chlorinated organic waste (e.g., PVC plastics, pesticides)	Highly toxic, linked to cancer and endocrine disruption
Heavy Metals (Pb, Hg, Cd, As, Cr, etc.)	Found in batteries, paints, electronic waste, medical waste	Bio accumulate in the environment, cause neurological damage
Volatile Organic Compounds (VOCs)	Evaporated chemicals from solvents, fuels, and industrial waste	Cause air pollution, some are carcinogenic

### Operation Mitigation / Control Measures

To reduce the release of harmful pollutants, the incinerator will include built in emission control technologies as describe below:

Project Activities	Potential Environmental Impacts	Mitigation Measures
Incineration of hazardous waste	<p><b>Air Quality:</b> Incomplete combustion due to low temperature or insufficient oxygen could lead to the release of harmful pollutants such as carbon monoxide (CO), VOCs, and particulate matter. These pollutants pose risks to human health and the environment.</p>	<p><b>Secondary Combustion Chamber</b> The secondary combustion chamber is designed to complete the combustion of any unburned gases that exit the main furnace. This ensures that harmful gases are fully decomposed and do not escape into the atmosphere.</p> <p>The secondary combustion chamber should always operate at temperatures above 1100°C to ensure the complete breakdown of hazardous substances. Monitoring and maintaining this temperature is critical.</p>
	<p><b>Toxic Emissions:</b> Inadequate combustion in the secondary chamber can produce toxic gases, including dioxins, furans, and other hazardous compounds.</p>	<p>By maintaining high temperature and sufficient retention time, the formation of these toxic compounds can be minimized or eliminated.</p> <p>Further, the operation will install continuous air quality monitoring systems to measure pollutants like CO, NOx, SOx, particulate matter, and dioxins. This allows operators to adjust the incineration parameters to ensure compliance with air quality standards.</p>

**Flue Gas Treatment**

**Water-Cooling Device:** the Operation will ensure that the cooling system operates efficiently to lower the temperature of the flue gas before further treatment. This minimizes thermal pollution and reduces the stress on downstream equipment.

**Wet Scrubber Technology:** Neutralize acidic gases (SO<sub>x</sub>, HCl)

Uses lime or water-based scrubbing solutions to remove sulfur oxides (SO<sub>x</sub>), hydrochloric acid (HCl), and particulate matter from the flue gas. The scrubber is designed to maximize the absorption of acidic gases and the removal of dust.

All wastewater from the scrubber system will be treated via chemical neutralization or advanced filtration technologies to remove contaminants before disposal.

**Continuous Filtration of Scrubber Water:**

The operation will implement a filtration and recycling system for the scrubber water to reduce water consumption and prevent wastewater contamination.

**Cyclone Dust Collector:**

The cyclone dust collector efficiently removes large dust particles, but smaller particles may still be emitted.

	<p><b>Water Pollution:</b> Wet scrubbers generate wastewater that can contain toxic residues, which need proper treatment and recycling to prevent contamination of water bodies.</p> <p><b>Soil and Groundwater Contamination:</b> Improper disposal of dust and sludge can lead to contamination of soil and groundwater.</p>	<p>Regular maintenance and monitoring of the cyclone dust collector will ensure that it operates at its highest efficiency. Periodic cleaning helps to avoid blockage and maintains the collector's performance.</p> <p>Recycling water in the scrubber and treating wastewater before disposal ensures minimal environmental impact on water quality.</p> <p>Incinerator bottom ash will be tested and analyzed following Table 1 before final disposal at Haags Bosch.</p> <p>Recovered sludge will return to the incinerator for destruction. Further, the operation will be conducted on an impervious surface.</p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## CONCLUSION:

The environmental impacts of incineration, including air pollution, water contamination, and soil pollution, can be mitigated effectively through a combination of advanced technologies, proper system maintenance, and continuous monitoring. Key mitigation measures include:

- Optimizing combustion conditions to ensure complete burning of waste.
- Implementing advanced gas cleaning systems (wet scrubbers, cyclone dust collectors) to remove pollutants.
- Recycling wastewater and properly managing waste to prevent contamination.
- Constantly monitoring emissions to ensure compliance with environmental standards.

When these measures are properly implemented, the environmental impact of the incineration process can be significantly reduced, making it a safer and more sustainable method of waste disposal.